

▶ MINI LINK HYDRAULIC SYSTEM

Precise metering straight to your die to save you money.

DESCRIPTION:

▶ SYSTEM FEATURES

The Mini Link Hydraulic System features a hydraulic meter and cylinder to drive the metering system, delivers an extremely consistent mix/meter of materials at low flow rates, ideal for low & high pressure applications, and more.

- Two magnetic proximity switches for rapid pump reversal change
- Fluid sections are constructed from stainless steel
- Adjustable for ratio variations
- Automatic 1:1 Pro Gun

▶ SPECIFICATIONS

Ratio:

- Two VHPC-2200: 1:1 TO 3.7:1
- VHPC-2200 & VHPC-3200-ADH: 1.84:1 TO 5.85:1
- VHPC-2200 & VHPC-4200: 4.15:1 TO 13:1

Metering Pumps:

- 120 Volt, 22 amp or 220V single phase, 13.7 amp (voltage must be specified on order)

Air Requirements:

- 20 CFM at 100 psi of clean dry air

Tanks:

- 15-gallon (57 liter) gravity feed (max fill load, 12-gallons each)

Flush Tank:

- 3-gallon (11 liter) pressure tank



▶ OPTIONS

- In-line Resin Heaters & Heated Hoses

Knoxville

Corporate Headquarters
2030 Falling Waters Rd., Suite 350
Knoxville, TN 37932
865-686-5670

Knoxville

Manufacturing Center
14542 El Camino Ln., Suite B
Lenoir City, TN 37771
865.686.5670

Knoxville

Machine Shop
642 Barbrow Lane
Knoxville, TN 37932
865-321-8809

Oldsmar

Service Center
146 Dunbar Avenue, Unit A
Oldsmar, FL 34677
727-573-2955

▶ For more information about adding the Mini Link Hydraulic System to your operation, or any of your adhesive dispensing needs, visit Magnum Venus Products at www.mvpind.com.