



▶ MINIPRO GELCOAT SYSTEM

The MiniPro Gelcoat System features reliable low pressure gelcoat delivery, easy setup, easy operation and easy maintenance with MVP's proven durability.

DESCRIPTION:

▶ SYSTEM FEATURES

Low pressure gelcoat delivery with ease of setup, operation, and maintenance. Rugged durability, fewer parts, and stainless steel construction of critical components combine to make the MiniPro Gelcoat System a versatile, portable production solution you can trust.

- Fewer parts to maintain
- Stainless steel where you need it
- Rugged design

▶ SPECIFICATIONS

MINIPRO GELCOAT SYSTEM

Output Capabilities: .75 LBS/MIN - 3 LBS/MIN
(.34 KGS/MIN - 1.36 KGS/MIN)

Avg. Air Consumption: 5 CFM (0.14 m³/MIN)

Catalyst % Range: 1.5% to 3.25% by volume

Available Pump Ratio: 22:1

Maximum Air Input Pressure: 100PSI (7BAR)

ADVANTAGE GELCOAT SYSTEM

Output Capabilities: .75 LBS/MIN - 3 LBS/MIN
(.34 KGS/MIN - 1.36 KGS/MIN)

Avg. Air Consumption: 5 CFM (0.14 m³/MIN)

Catalyst % Range: 1.5% to 3.25% by volume

Available Pump Ratio: 22:1

Maximum Air Input Pressure: 100PSI (7BAR)



▶ OPTIONS

Heaters

- CFH Series

Catalyst

Alarms

- CTS-9000

Mixers

- M-AGD

Guns

- TLN Series
- AT Series

Knoxville

Corporate Headquarters
2030 Falling Waters Rd., Suite 350
Knoxville, TN 37932
865-686-5670

Knoxville

Manufacturing Center
14542 El Camino Ln., Suite B
Lenoir City, TN 37771
865.686.5670

Knoxville

Machine Shop
642 Barbrow Lane
Knoxville, TN 37932
865-321-8809

Oldsmar

Service Center
146 Dunbar Avenue, Unit A
Oldsmar, FL 34677
727-573-2955

▶ For more information about adding the MiniPro Gelcoat System to your operation, or any of your adhesive dispensing needs, visit Magnum Venus Products at www.mvpind.com.