



## ▶ ULTRAMAX™ GELCOAT SYSTEM

Fewer and durable parts, stainless steel where you need it, and a rugged design, combine to reduce parts cost and down time.

### DESCRIPTION:

#### ▶ SYSTEM FEATURES

Magnum Venus Products' (MVP) UltraMAX Gelcoat System features low pressure with easy setup, easy operation and easy maintenance along with MVP's renowned durability, all of which unite to deliver the composites industry a reliable workhorse.

This machine allows the operator to adjust the preferred catalyst setting with ease. Infinite catalyst settings are available with a simple

adjustment. Available in Internal & External Mix

#### Configurations

- Modular Versatility
- Rugged Components

#### ▶ SPECIFICATIONS

##### ULTRAMAX™ GELCOAT SYSTEM

Output Capabilities: 2 LBS/MIN - 8 LBS/MIN  
(.907 KGS/MIN - 3.63 KGS/MIN)

Avg. Air Consumption: 8 CFM (0.23 m<sup>3</sup>/MIN)

Catalyst % Range: 1% to 4% by volume

Available Pump Ratios: 11:1, 20:1 & 30:1

Maximum Air Input Pressure: 100 PSI (7BAR)

#### ▶ OPTIONS

##### Heaters

- CFH Series

##### Monitors

- CB-8000

##### Catalyst Alarms

- CTS-9000

##### Mixers

- M-AGD

##### Guns

- TLN Series
- PRO Series
- AT Series



#### Knoxville

Corporate Headquarters  
2030 Falling Waters Rd., Suite 350  
Knoxville, TN 37932  
**865-686-5670**

#### Knoxville

Manufacturing Center  
14542 El Camino Ln., Suite B  
Lenoir City, TN 37771  
**865.686.5670**

#### Knoxville

Machine Shop  
642 Barbrow Lane  
Knoxville, TN 37932  
**865-321-8809**

#### Oldsmar

Service Center  
146 Dunbar Avenue, Unit A  
Oldsmar, FL 34677  
**727-573-2955**

▶ For more information about adding the UltraMax Gelcoat System to your operation, or any of your adhesive dispensing needs, visit Magnum Venus Products at [www.mvpind.com](http://www.mvpind.com).